



E100 EXTENDED

Universal-Abzieher Easy-Fix mit langen Haken, 2-armig

- Das Schnellspannsystem Easy-Fix ermöglicht ein effizientes und zeitsparendes Einstellen der Spannweite
- Robuste, im Gesenk geschmiedete Ausführung
- Kräftige Spindel mit Feingewinde und auswechselbarer Zentrierkugel
- Umsteckbare Abzugshaken für den Einsatz als Außen- oder Innenabzieher
- Unterschiedliche Hakenlängen für die optimale Anpassung an die erforderliche Spanntiefe
- Eine Hydraulikspindel kann optional nachgerüstet werden (s. Tabelle)

Universal-Puller Easy-Fix with extended legs, 2-arms

- The rapid clamping system Easy-Fix enables an efficient and time saving adjustment of the puller legs
- Robust drop-forged design
- Strong spindle with fine thread and replaceable ball on top for optimal centering
- Reversible puller legs for use as external or internal puller
- Legs in various length, for ideal adaption to the necessary clamping depth
- Hydraulic spindles as upgrade available (see table)



No.												
E100-1-12		20-90	120	80	4,5	M14x1,5x130	17	3	13	25	20	1,1
E100-1-20		20-90	200	80	4,5	M14x1,5x130	17	3	13	25	20	1,5
E100-1-25		20-90	250	80	4,5	M14x1,5x130	17	3	13	25	20	1,7
E100-1,5-12		25-130	120	80	4,5	M14x1,5x130	17	3	13	25	20	1,3
E100-1,5-20		25-130	200	80	4,5	M14x1,5x130	17	3	13	25	20	1,7
E100-1,5-25		25-130	250	80	4,5	M14x1,5x130	17	3	13	25	20	1,9
E100-2-22	●	50-160	220	150	6,5	G1/2"x14x210	22	●	4	16	35	3,5
E100-2-30	●	50-160	300	150	6,5	G1/2"x14x210	22	●	4	16	35	4,0
E100-2,5-22	●	60-200	220	150	6,5	G1/2"x14x210	22	●	4	16	35	3,8
E100-2,5-30	●	60-200	300	150	6,5	G1/2"x14x210	22	●	4	16	35	4,3
E100-3-30	●	80-250	300	320	11	G3/4"x14x280	27	●	5	25	54	9,2
E100-3-40	●	80-250	400	320	11	G3/4"x14x280	27	●	5	25	54	10,5
E100-3-50	●	80-250	500	320	11	G3/4"x14x280	27	●	5	25	54	11,9
E100-3,5-30	●	80-350	300	320	11	G3/4"x14x280	27	●	5	25	54	10,3
E100-3,5-40	●	80-350	400	320	11	G3/4"x14x280	27	●	5	25	54	11,6
E100-3,5-50	●	80-350	500	320	11	G3/4"x14x280	27	●	5	25	54	13,0
E100-4-30	●	110-520	300	360	13	G3/4"x14x280	27	●	5	25	54	14,8
E100-4-40	●	110-520	400	360	13	G3/4"x14x280	27	●	5	25	54	16,1
E100-4-50	●	110-520	500	360	13	G3/4"x14x280	27	●	5	25	54	17,5
E100-4,5-30	●	140-640	300	360	13	G3/4"x14x280	27	●	5	25	54	17,5
E100-4,5-40	●	140-640	400	360	13	G3/4"x14x280	27	●	5	25	54	18,8
E100-4,5-50	●	140-640	500	360	13	G3/4"x14x280	27	●	5	25	54	20,2